



WIRELESS G NETWORK CAMERA

Remote Video Monitoring and Recording

Motion JPEG (MJPEG) for Higher Quality Recording and Monitoring

1.0 Lux Sensor Can Capture Video In Low-Light Conditions



The D-Link® Wireless G Network Camera (DCS-920) connects to a wireless (or wired) network to provide remote high-quality video surveillance. With its sleek compact design, the DCS-920 is an affordable network camera ideal for your home or small business. Since the DCS-920 is a wireless camera, you can place it in areas that have no access to an Ethernet (wired) connection, such as ceilings or high walls. Additionally, with support for WPA®-PSK and WPA2®, the DCS-920 provides you with the highest level of security when connecting to your wireless network, enabling you to stream high-quality MJPEG video quickly and easily to your computer.

EASY NETWORK SETUP

The DCS-920 adheres to the Universal Plug & Play (UPnP®) specification, which allows for automatic detection and addition to a network. Once recognized by your network, the DCS-920 can be accessed and viewed from "My Network Places" as a device on your network. You can then keep an eye out on your kids, pets, home or office by simply logging onto the DCS-920 web interface using a Java™-based browser from any computer with Internet access, even away from home.

CAMERA MANAGEMENT

For advanced users that want more out of their camera, the DCS-920 also comes with D-Link D-ViewCam™ 2.0 management software. D-ViewCam comes with a host of features including the ability to record directly from the camera to a local hard drive, trigger motion detection, set recording schedules, set e-mail alert notifications, and even support for up to 32 cameras. D-ViewCam also allows you to upload a floor plan of your home or small business and create a realistic layout of where your cameras are located, providing you with better access to your camera.

With features such as MJPEG video streaming, wireless connectivity, and D-ViewCam™ 2.0 management, the D-Link Wireless G Network Camera (DCS-920) is a cost-effective and versatile security solution for your home or small business.



WHAT THIS PRODUCT DOES

The D-Link® Wireless G Network Camera (DCS-920) is a versatile surveillance solution that connects to your wireless (or wired) network to provide monitoring for your home or small office. With the DCS-920 installed, you can then keep an eye out on your kids, pets, home, or office from a Java™-enabled web browser such as Internet Explorer®.

YOUR NETWORK SETUP



TECHNICAL SPECIFICATIONS

CAMERA SPECIFICATIONS

- + Sensor: VGA ¼" CMOS
- + Lens: 5.01mm, F2.8
- + Minimum Illumination: 1.0 Lux @ F2.8
- + 3A Control: AGC, AWB, AES
- + Electronic Shutter: 1/60(1-50) ~ 1/15,000 Sec

VIDEO FORMATS SUPPORTED

- + MJPEG Compression
- + JPEG for Still Image

REMOTE MANAGEMENT

- + D-ViewCam™ 2.0 Allows for Remote Management and Control of up to 32 Network Cameras
- + Web-based

RESOLUTION

- + Up to 15fps at 640x480
- + Up to 30fps at 320x240
- + Up to 30fps at 160x120

CONNECTIVITY

- + Wireless (802.11g)
- + Wired (10/100 Fast Ethernet)

NETWORKING PROTOCOLS

- + IPv4, ARP, TCP, UDP, ICMP
- + DHCP Client
- + NTP Client
- + DDNS Client
- + SMTP Client
- + FTP Client
- + HTTP Server
- + DNS Client
- + PPPoE
- + RTP
- + LLTD

STANDARDS

- + IEEE 802.11g
- + IEEE 802.3
- + IEEE 802.3x Flow Control
- + IEEE 802.11b
- + IEEE 802.3u

MINIMUM SYSTEM REQUIREMENTS

- + Wired (10/100 Fast Ethernet) or 802.11g Wireless Network
- + Computer with
 - 1.3GHz Processor
 - 128MB Memory
 - Windows Vista®3 or Windows® XP SP2
 - Internet Explorer® v6 or later

Multiple Camera Operation Requires

- + Computer with:
 - 2.4GHz Processor
 - 512MB Memory
 - 32MB Video Card
 - Windows Vista®3 or Windows® XP SP2
 - Internet Explorer® v6 or later

SECURITY

- + Wireless: WPA®, WPA2®
- + Default Admin ID/Password Admin

LEDs

- + Link/Power
- + WPS

CERTIFICATIONS

- + FCC Class B
- + IC
- + CE

POWER

- + External Power Supply: 5V, 2.5A
- + Consumption: 4.5 Watts Max

OPERATING TEMPERATURE

32°F to 104°F (0°C to 40°C)

STORAGE TEMPERATURE

-4°F to 158°F (-20°C to 70°C)

OPERATING HUMIDITY

20%-80% RH Non-condensing

DIMENSIONS (W X D X H)

- + Item: 2.8" x 4.3" x 1.5" (71.1mm x 109.2mm x 38.1mm)
- + Packaging: 8.2" x 10.8" x 2.7" (202.3mm x 274.3mm x 68.6mm)

WEIGHT

- + Item: 0.5 lbs (0.23 kg)
- + Packaging: 2.0 lbs (0.91 kg)

WARRANTY

1-Year Limited¹

PACKAGE CONTENTS

- + Wireless G Network Camera
- + Detachable Antenna
- + CAT5 Ethernet Cable
- + Power Adapter
- + Mounting Kit
- + Quick Installation Guide
- + CD-ROM² with
 - Software
 - Product Documentation

SECURITY

¹ 1-Year Limited Warranty available only in the USA and Canada.
² Latest software and documentation are available at <http://support.dlink.com>.
³ Computer must adhere to Microsoft's minimum system requirements.

Use of video equipment for recording the image of a person without their knowledge and consent is prohibited in certain states or jurisdictions. Nothing herein represents a warranty or representation that the D-Link product provided herein is suitable for the end-user's intended use under the applicable laws of his or her state. D-Link disclaims any liability whatsoever for any end-user use of the D-Link product which fails to comply with applicable state, local or federal laws. All references to speed are for comparison purposes only. Product specifications, size and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

©2008-2009 D-Link Corporation/D-Link Systems, Inc. All rights reserved. D-Link, the D-Link logo, the Securicam logo, and D-ViewCam are trademarks or registered trademarks of D-Link Corporation or its subsidiaries in the United States and/or other countries. Other trademarks or registered trademarks are the property of their respective owners. Visit www.dlink.com for more details.